

Power system DPS 4000B-48-48

Description

The DPS 4000B-48-48 is based on Delta DPR 4000B EnergE rectifiers. It belongs to the Delta CabD product series. This energy efficient, high power density system is ideal for space critical applications. An integrated modular system allows flexible and adaptable installations.

The system includes up to forty-eight rectifiers, AC and DC connections, battery connection and the Delta PSC 3 controller. In addition, easy installation and expandability add to the success of the system.

Delta is known for quality and product reliability, and to this solution has been added cost-effectiveness.

Main features

- DPR 4000B-48 EnergE rectifiers
 - Efficiency 95 %
 - Remarkable cost savings of cooling
- Up to 192 kW
- Separate battery and distribution cabinets
- Expandable with a 2nd system
- Power system controller PSC 3

Applications

- Core network components
- Telecommunications and data networks



Our product portfolio includes both indoor and outdoor power systems building on extensive R&D, modular production and customization. InD and OutD categories with CellD, MidD and CabD series can meet any of your size and location requirements.

CabD series can secure up to hundreds of kW of premium-quality electricity. The modularity and scalability of the systems enable fast roll-out and ease of expansion when needed. CabD offers the option of parallel installation for maximum capacity. The entire system can be controlled by a single unit.



Technical specifications

1. Input	
AC connection	(3L + N + PE)
Nominal voltage	3 x 230 V _{RMS} (L-N)
Voltage range	88 - 300 V _{RMS}
Frequency range	45 - 66 Hz
Current nominal	3 x 293 A _{RMS} @ 192kW
Mains terminal	Main breaker 4P 400A
Input protection, recom.	3 x 400 A (3~)
Transient OVP	Option

2. Output	
Voltage range	42 - 58 V _{DC} ; 53.5 V _{DC nom}
Power, nominal	192 kW
One row in 2200 mm high cabinet (See for distribution units)	3 x DFU 30 x MCB 2 x DFU 20 x MCB
PLD	Option
Battery circuit breaker	4 x 1500 A
LVD	No

Ordering information	
Product line number	3791140100
Description	DPS 4000B-48-48

3. General	
Height, overall	2000 mm
Width, body	1800 mm
Depth, overall	600 mm
Weight, system	~ 750 kg
Efficiency	95 %
Ambient temperature	-5 to +45 °C
Relative humidity	95 % max, non cond.
Safety	IEC/EN 60950
EMC	EN 300 386
Protection	IP 20
Controller	PSC 3
Rectifier	DPR 4000B-48

Subject to change without notice.



Delta Energy Systems (Finland) Oy
Juvan teollisuuskatu 15, FIN-02921 Espoo
Phone: +358 9 849 660, Fax: +358 9 8496 6100

www.deltapowersolutions.com